

Product Guide

UV
Lighting



UV-125

UV-160

UV-400

- A new concept of UV lighting.
- Wide angle dispersion.
- Easy lamp replacement.

| Model | UV-125 | UV-160 | UV-400 | |
|------------|-----------------------------------|-----------------------------------|--|-------------------------------|
| Power | AC 230-250V 50Hz | | AC 230-250V 50Hz | AC 120V 60Hz |
| Fuse | 20mm Glass T5A Fast Blow | | 20mm Glass T5A Fast Blow | 20mm Glass T6.3A Fast Blow |
| Lamp | XPW-125 | XPW-160 | XPW-400 | |
| Dimensions | 225x248x248mm 8.86x9.76x9.76in | 225x248x248mm 8.86x9.76x9.76in | 365 x 328 x 328 mm 14.37 x 12.9 x 12.9 in | |
| Weight | 5.5 kg / 12.1 lbs | 3 kg / 6.6 lbs | 11 kg / 24.2 lbs | |

⚠ Caution:

- This unit is designed for indoor use only. Always keep the unit dry at all times.
- Please make sure the source voltage in your area matches the required voltage.
- No power switch, plug the unit in, the lamp will immediately begin to glow.
- Always replace with same type lamp and fuse.
- For safety, disconnect mains power when not using.
- High voltage! Don't open the fixture for repair or replacing part purpose while the power is on.

CE